

屋内照明器具特性	
品番(品名)	LGB19631K
光源	LDA13L-G/Z100E/S/W ×6 1520.0 l m
管理番号	K0168443(0)DB1
BZ分類	BZ8

器具効率	89%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	43%	床	10%				10%				10%				10%				0%		
下方光束	46%		10%				10%				10%				10%				0%		
保守率	良 0.67 中 0.63 否 0.56	室指数	照明率 (X0.01)																ZCM		
			0.6	40	29	22	18	37	27	21	16	31	23	18	14	25	19	15		11	7
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	0.8	48	37	29	24	44	34	27	22	36	29	23	19	29	23	19	16	10
				1.0	53	42	35	29	48	39	32	27	40	33	27	23	32	27	23	19	12
取付高さ	器具間隔最大限		Hm	1.25	58	48	40	35	53	44	37	32	44	37	32	27	35	30	26	23	15
	横方向(A)	縦方向(B)		1.5	61	52	45	39	56	48	41	36	47	40	35	31	38	33	29	26	17
Hm	1.36Hm	1.30Hm	2.0	66	58	51	46	61	53	48	43	51	45	40	36	41	37	33	30	20	
			2.5	69	62	56	51	64	57	52	47	53	48	44	40	44	40	37	34	23	
			3.0	71	65	60	55	66	60	55	51	55	51	47	44	46	42	39	36	25	
			4.0	75	69	64	60	69	64	60	56	58	54	51	48	48	45	43	40	28	
			5.0	77	72	68	64	71	67	63	60	60	57	54	51	50	47	45	43	30	
			7.0	79	75	72	69	73	70	67	64	62	60	57	55	52	50	48	46	33	
			10.0	81	78	76	73	75	73	70	68	64	62	60	59	54	52	51	49	36	

