

# 屋内照明器具特性

品番 (品名)	LGB50155				
光源	LGB50150 ×1                      302.0 l m				
管理番号	K0121394 (0) DB 1				
BZ分類	BZ4/0.7/BZ3/1.8/BZ4				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束	1 %	反射率	床	10 %				10 %				10 %				10 %				0 %		
下方光束	99 %		室指数	照明率 ( X0.01)                      ZCM																		
保守率	良 0.69 中 0.67 否 0.63	0.6	61	50	42	38	60	49	42	37	57	48	42	37	55	47	41	37	35			
		0.8	71	61	54	48	70	60	53	48	67	59	53	48	65	57	52	48	46			
		1.0	78	68	61	56	76	67	61	56	73	66	60	56	71	64	59	55	53			
		1.25	83	75	68	63	82	74	68	63	79	72	67	63	76	70	66	62	60			
下方投影面積	c m <sup>2</sup>	1.5	87	79	73	69	85	78	73	68	82	76	72	68	80	75	70	67	65			
		2.0	92	86	80	76	90	84	80	76	87	82	78	75	85	80	77	74	71			
取付高さ	器具間隔最大限		2.5	95	90	85	81	93	88	84	81	90	86	83	79	88	84	81	78	76		
	横方向 (A)	縦方向 (B)	3.0	97	92	88	85	95	91	87	84	93	89	86	83	90	87	84	82	79		
H m	1.21 H m	1.21 H m	4.0	100	96	93	90	98	95	92	89	95	92	90	87	93	90	88	86	83		
			5.0	101	98	95	93	100	97	94	92	97	95	92	90	94	92	91	89	86		
			7.0	103	101	99	97	102	100	98	96	99	97	95	94	96	95	93	92	89		
			10.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92		

