

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK41719J + NEL4600HN       |
| 光源       | LED5000_85_6680 ×1 6680.0 lm |
| 管理番号     | K0192152 (0) D 1             |
| BZ分類     | BZ5                          |

| 器具効率             |           | 100 %                              | 天井<br>壁<br>床 | 80 %              |     |     |    | 70 % |     |     |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |  |
|------------------|-----------|------------------------------------|--------------|-------------------|-----|-----|----|------|-----|-----|----|------|----|----|----|------|----|----|----|-----|--|--|
|                  |           |                                    |              | 70                | 50  | 30  | 10 | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |  |
|                  |           |                                    |              | 10 %              |     |     |    | 10 % |     |     |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |  |
| 上方光束<br>下方光束     |           | 100 %                              | 反射率          | 照明率 ( X0.01 ) ZCM |     |     |    |      |     |     |    |      |    |    |    |      |    |    |    |     |  |  |
| 保守率              |           | 良<br>中<br>否                        | 0.6          | 57                | 45  | 37  | 31 | 55   | 44  | 36  | 31 | 53   | 43 | 36 | 31 | 51   | 42 | 36 | 31 | 29  |  |  |
|                  |           |                                    | 0.8          | 67                | 55  | 47  | 42 | 65   | 55  | 47  | 42 | 63   | 53 | 46 | 41 | 60   | 52 | 46 | 41 | 39  |  |  |
|                  |           |                                    | 1.0          | 73                | 63  | 55  | 49 | 72   | 62  | 55  | 49 | 69   | 60 | 54 | 49 | 66   | 59 | 53 | 48 | 46  |  |  |
|                  |           |                                    | 1.25         | 79                | 70  | 62  | 57 | 78   | 69  | 62  | 57 | 75   | 67 | 61 | 56 | 72   | 65 | 60 | 56 | 53  |  |  |
| 下方投影面積<br>等価発光面積 |           | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5          | 84                | 75  | 68  | 62 | 82   | 74  | 67  | 62 | 79   | 72 | 66 | 62 | 76   | 70 | 65 | 61 | 59  |  |  |
|                  |           |                                    | 2.0          | 89                | 82  | 76  | 71 | 88   | 81  | 75  | 71 | 85   | 79 | 74 | 70 | 82   | 77 | 73 | 69 | 67  |  |  |
| 取付<br>高さ         | 器具間隔最大限   |                                    | 2.5          | 93                | 87  | 81  | 77 | 91   | 86  | 81  | 76 | 88   | 83 | 79 | 75 | 86   | 81 | 78 | 74 | 72  |  |  |
|                  | 横方向 ( A ) | 縦方向 ( B )                          | 3.0          | 95                | 90  | 85  | 81 | 94   | 89  | 84  | 81 | 91   | 87 | 83 | 80 | 88   | 85 | 81 | 78 | 76  |  |  |
| 1.5m             | 1.99 m    | 2.12 m                             | 4.0          | 99                | 94  | 90  | 87 | 97   | 93  | 90  | 86 | 94   | 91 | 88 | 85 | 92   | 89 | 86 | 84 | 81  |  |  |
| 2                | 2.62      | 2.66                               | 5.0          | 101               | 97  | 94  | 91 | 99   | 96  | 93  | 90 | 96   | 94 | 91 | 89 | 94   | 91 | 89 | 87 | 85  |  |  |
| 2.5              | 3.26      | 3.22                               | 7.0          | 103               | 100 | 98  | 95 | 101  | 99  | 97  | 95 | 99   | 97 | 95 | 93 | 96   | 95 | 93 | 91 | 89  |  |  |
| 3                | 3.89      | 3.8                                | 10.0         | 104               | 103 | 101 | 99 | 103  | 101 | 100 | 98 | 101  | 99 | 98 | 96 | 98   | 97 | 96 | 95 | 92  |  |  |

