

屋内照明器具特性

品番 (品名)	LGB50431K									
光源	LED3500_70_2446 x1					2446.0 lm				
管理番号	K0147494(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	3%	室指数	照明率 (X0.01)																ZCM	
下方光束	97%																			
保守率	良 中 否	0.69	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.1	3.4	3.0	2.8
		0.67	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.8	5.0	4.4	4.0	3.7
			1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.7	5.9	5.2	4.7	6.4	5.7	5.1	4.7	4.4
		0.63	1.25	7.8	6.9	6.1	5.5	7.7	6.7	6.1	5.5	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.4	5.1
下方投影面積	c m ²	1.5	8.3	7.4	6.7	6.1	8.1	7.2	6.6	6.1	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.6	
		2.0	8.8	8.1	7.4	6.9	8.6	7.9	7.4	6.9	8.3	7.7	7.2	6.8	7.9	7.4	7.0	6.6	6.3	
取付高さ	器具間隔最大限		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.4	8.6	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.8
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.4	7.9	9.2	8.7	8.3	7.9	8.9	8.4	8.0	7.7	8.5	8.2	7.8	7.5	7.2
1.5m	1.91m	2.12m	4.0	9.7	9.3	8.9	8.5	9.5	9.1	8.8	8.4	9.2	8.8	8.5	8.2	8.9	8.6	8.3	8.1	7.7
2	2.52	2.68	5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.1	8.8	8.6	8.4	8.1
2.5	3.13	3.26	7.0	10.1	9.9	9.6	9.4	10.0	9.7	9.5	9.2	9.6	9.4	9.2	9.0	9.3	9.1	9.0	8.8	8.5
3	3.74	3.86	10.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.8	9.7	9.5	9.4	9.5	9.4	9.3	9.1	8.8

