

屋内照明器具特性	
品番 (品名)	LGB15111WZ
光源	LDA4L-G-E17/Z40E/S/W/2 ×1 440.0 1m
管理番号	K0111933(2)DB1
BZ分類	BZ7

器具効率	84%	天井	80%				70%				50%				30%				0%	
	上方光束 29%		下方光束 55%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01) ZCM																			
保守率	良	0.63	0.6	4.0	2.9	2.3	1.8	3.7	2.8	2.1	1.7	3.2	2.5	1.9	1.5	2.8	2.2	1.7	1.4	1.0
	中	0.6	0.8	4.7	3.7	3.0	2.5	4.4	3.5	2.8	2.3	3.8	3.1	2.5	2.1	3.3	2.7	2.2	1.9	1.4
	否	0.56	1.0	5.2	4.2	3.5	3.0	4.9	4.0	3.3	2.8	4.3	3.5	3.0	2.6	3.7	3.1	2.6	2.3	1.8
			1.25	5.7	4.8	4.1	3.5	5.3	4.5	3.9	3.4	4.7	4.0	3.5	3.0	4.0	3.5	3.1	2.7	2.1
下方投影面積	c m <sup>2</sup>		1.5	6.0	5.2	4.5	4.0	5.7	4.9	4.3	3.8	4.9	4.3	3.8	3.4	4.3	3.8	3.4	3.0	2.4
等価発光面積	c m <sup>2</sup>		2.0	6.5	5.8	5.1	4.6	6.1	5.4	4.9	4.4	5.4	4.8	4.4	4.0	4.7	4.2	3.9	3.5	2.8
取付高さ	器具間隔最大限		2.5	6.8	6.2	5.6	5.1	6.4	5.8	5.3	4.9	5.6	5.2	4.7	4.4	4.9	4.5	4.2	3.9	3.1
	横方向 (A)	縦方向 (B)	3.0	7.0	6.4	5.9	5.5	6.6	6.1	5.6	5.2	5.9	5.4	5.0	4.7	5.1	4.8	4.5	4.2	3.4
H m	1.41 H m	1.41 H m	4.0	7.3	6.8	6.4	6.0	6.9	6.5	6.1	5.7	6.1	5.8	5.4	5.1	5.4	5.1	4.8	4.6	3.7
			5.0	7.5	7.1	6.7	6.4	7.1	6.7	6.4	6.1	6.3	6.0	5.7	5.5	5.6	5.3	5.1	4.9	4.0
			7.0	7.8	7.4	7.1	6.8	7.3	7.0	6.8	6.5	6.5	6.3	6.1	5.9	5.8	5.6	5.4	5.2	4.3
			10.0	7.9	7.7	7.4	7.2	7.5	7.3	7.1	6.9	6.7	6.5	6.4	6.2	6.0	5.8	5.7	5.5	4.6

