

屋内照明器具特性

品番 (品名)	NTN83510									
光源	LED5000_70_1700 x1 1700.0 lm									
管理番号	K0167965(0)DY1									
BZ分類	BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	19%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	81%																																																						
保守率	良 中 否	0.69	0.6	51	38	30	25	49	37	29	24	44	34	28	23	40	32	26	22	19																																			
		0.67	0.8	60	48	40	34	57	46	38	33	52	43	36	31	48	40	34	29	26																																			
			1.0	66	55	46	40	63	53	45	39	58	49	42	37	53	45	40	35	31																																			
		0.63	1.25	72	61	53	47	69	59	52	46	63	55	48	43	57	51	45	41	36																																			
下方投影面積	c m ²	1.5	76	66	58	52	73	64	57	51	67	59	53	48	61	55	50	45	40																																				
		2.0	82	73	66	60	78	71	64	59	72	65	60	55	66	61	56	52	46																																				
取付高さ	器具間隔最大限		2.5	85	78	72	66	82	75	69	64	75	70	65	61	69	65	61	57	51																																			
	横方向 (A)	縦方向 (B)	3.0	88	81	76	71	85	78	73	68	78	73	68	65	72	68	64	61	54																																			
1.5m	2.06m	1.93m	4.0	91	86	81	77	88	83	78	74	81	77	73	70	75	72	69	66	59																																			
2	2.74	2.54	5.0	94	89	85	81	90	86	82	78	84	80	77	74	77	74	72	69	62																																			
2.5	3.46	3.15	7.0	96	93	89	86	93	89	86	83	86	83	81	78	80	78	76	74	66																																			
3	4.12	3.76	10.0	98	96	93	90	95	92	90	88	88	86	84	82	82	80	79	77	69																																			

