

# 屋内照明器具特性

品番 (品名)	LGB51690									
光源	LED2700_70_527 x1					527.0 lm				
管理番号	K0134923 (1) DB1									
BZ分類	BZ3/3.5/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		88%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m <sup>2</sup>		1.25	82	75	69	64	80	73	67	63	76	70	65	61	72	67	63	60	56	
	等価発光面積		c m <sup>2</sup>	1.5	86	79	73	69	83	77	72	68	79	73	69	66	75	70	67	64	60
取付高さ	器具間隔最大限		2.5	93	88	83	80	90	86	82	78	86	82	78	76	81	78	75	73	68	
	横方向 (A)	縦方向 (B)	3.0	95	90	86	83	92	88	85	81	88	84	81	78	83	80	78	76	71	
H m	1.22 H m	1.22 H m	4.0	97	94	90	87	95	91	88	86	90	87	85	82	85	83	81	79	74	
			5.0	99	96	93	90	96	93	91	89	91	89	87	85	87	85	83	82	76	
			7.0	101	98	96	94	98	96	94	92	93	91	90	88	89	87	86	85	79	
			10.0	102	100	99	97	99	98	96	95	95	93	92	91	90	89	88	87	81	

