

# 屋内照明器具特性

品番 (品名)	LGB54150K														
光源	LDA7L-G-E17/Z60E/S/W/2 x1										760.0 1m				
管理番号	K0157124(0)DR1														
BZ分類	BZ5/0.7/BZ4/2.8/BZ3														

器具効率	50%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 ( X0.01)																ZCM		
下方光束	50%																				
保守率	良 中 否	0.67	0.6	28	22	18	15	27	22	18	15	26	21	18	15	25	21	17	15	14	
		0.63	0.8	34	28	24	22	33	28	24	22	32	27	24	21	31	27	24	21	20	
			1.0	38	33	29	26	37	32	29	26	35	31	28	26	34	31	28	26	25	
		0.56	1.25	41	36	33	31	40	36	33	30	39	35	32	30	37	34	32	30	29	
下方投影面積	c m <sup>2</sup>	1.5	43	39	36	34	42	39	36	33	41	38	35	33	40	37	35	33	32		
		2.0	46	43	40	38	45	42	40	38	44	41	39	37	42	40	38	37	36		
取付高さ	器具間隔最大限		2.5	47	45	43	41	47	44	42	40	45	43	41	40	44	42	41	39	38	
	横方向 (A)	縦方向 (B)	3.0	49	46	44	43	48	46	44	42	47	45	43	42	45	44	42	41	40	
H m	1.87 H m	1.87 H m	4.0	50	48	47	45	49	48	46	45	48	47	45	44	47	46	45	44	42	
			5.0	51	49	48	47	50	49	48	46	49	48	47	46	48	47	46	45	44	
			7.0	52	51	50	49	51	50	49	48	50	49	48	47	49	48	47	47	45	
			10.0	52	52	51	50	52	51	50	50	51	50	49	49	49	49	48	48	47	

