

# 屋内照明器具特性

品番 (品名)	LGB54348	
光源	LED2700_70_838 ×1	838.0 lm
管理番号	K0135903(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	101%	床	10%				10%				10%				10%				0%				
室指数			照明率 ( X0.01 )																ZCM				
保守率	良 0.67	0.6	0.6	86	80	76	73	85	79	76	73	84	79	76	73	83	78	75	73	72			
	中 0.63		0.8	92	86	83	80	91	86	83	80	89	85	82	80	88	84	82	80	78			
	否 0.56		1.0	95	91	87	85	94	90	87	84	93	89	86	84	91	88	86	84	82			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	98	94	91	89	97	93	91	88	95	92	90	88	94	91	89	87	86		
				1.5	100	96	94	91	99	96	93	91	97	94	92	90	96	93	91	90	88		
取付高さ	器具間隔最大限		Hm	0.42Hm	0.42Hm	2.5	104	101	99	97	103	100	99	97	101	99	97	96	99	97	96	95	93
	横方向 (A)	縦方向 (B)				3.0	105	103	101	99	104	102	100	99	102	100	99	97	100	98	97	96	94
Hm	0.42Hm	0.42Hm	4.0	106	104	103	101	105	103	102	101	103	101	100	99	101	100	99	98	96			
			5.0	107	105	104	103	105	104	103	102	103	102	101	101	101	101	101	100	99	97		
Hm	0.42Hm	0.42Hm	7.0	107	106	105	105	106	105	104	104	104	103	103	102	102	101	101	100	98			
			10.0	108	107	107	106	107	106	106	105	105	104	104	103	103	102	102	101	99			

