

屋内照明器具特性	
品番 (品名)	LGB53004
光源	LED2700_70_1500 x1 1500.0 lm
管理番号	K0141000(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	12%	床	10%				10%				10%				10%				0%				
下方光束	88%	室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	54	42	34	28	52	41	33	28	48	38	32	27	45	37	31	26	24				
		0.8	63	52	44	38	61	50	43	37	57	48	41	36	53	45	39	35	32				
		1.0	70	59	51	45	67	57	50	44	63	54	48	43	59	51	46	41	38				
		1.25	76	66	58	52	73	64	57	51	68	60	54	49	64	57	52	48	44				
下方投影面積	c m ²	1.5	80	70	63	57	77	69	62	56	72	65	59	55	67	61	57	53	48				
		2.0	85	77	71	66	83	75	69	64	77	71	66	62	73	68	63	60	55				
取付高さ	器具間隔最大限		2.5	89	82	76	71	86	80	75	70	81	76	71	67	76	72	68	65	60			
	横方向 (A)	縦方向 (B)	3.0	91	85	80	76	89	83	78	74	83	79	75	71	79	75	71	68	63			
1.5m	1.89m	1.91m	4.0	95	90	85	82	92	87	84	80	87	83	80	77	82	79	76	74	68			
2	2.49	2.53	5.0	97	93	89	86	94	90	87	84	89	86	83	80	84	81	79	77	71			
2.5	3.12	3.16	7.0	99	96	93	90	96	94	91	88	91	89	87	85	86	84	83	81	75			
3	3.74	3.79	10.0	101	99	96	94	98	96	94	92	93	91	90	88	88	87	86	84	78			

