

屋内照明器具特性

品番 (品名)	LGB57663															
光源	LDA7L-G/Z60E/S/W/2 ×6 810.0 1 m															
管理番号	K0165036(0)D 1															
BZ分類	BZ8/0.7/BZ7															

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	31 %																			
下方光束	63 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.67 中 0.63 否 0.56	0.6	4.4	3.2	2.4	1.9	4.1	3.0	2.3	1.8	3.6	2.7	2.0	1.6	3.1	2.3	1.8	1.4	1.0	
		0.8	5.2	4.0	3.2	2.6	4.8	3.8	3.0	2.5	4.2	3.3	2.7	2.2	3.6	2.9	2.4	2.0	1.5	
		1.0	5.7	4.6	3.8	3.1	5.4	4.3	3.6	3.0	4.7	3.8	3.2	2.7	4.0	3.3	2.8	2.4	1.8	
		1.25	6.3	5.2	4.4	3.7	5.9	4.9	4.1	3.6	5.1	4.3	3.7	3.2	4.4	3.8	3.3	2.9	2.2	
下方投影面積	c m ²	1.5	6.6	5.6	4.9	4.2	6.2	5.3	4.6	4.0	5.4	4.7	4.1	3.6	4.7	4.1	3.6	3.2	2.5	
		2.0	7.2	6.3	5.6	5.0	6.8	6.0	5.3	4.7	5.9	5.3	4.7	4.3	5.2	4.7	4.2	3.8	3.0	
		2.5	7.5	6.8	6.1	5.5	7.1	6.4	5.8	5.3	6.3	5.7	5.2	4.8	5.5	5.0	4.6	4.3	3.4	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.41 H m	1.41 H m	4.0	8.2	7.6	7.1	6.6	7.7	7.2	6.7	6.3	6.8	6.4	6.0	5.7	6.0	5.7	5.4	5.1	4.1
			5.0	8.4	7.9	7.4	7.0	7.9	7.5	7.1	6.7	7.1	6.7	6.3	6.0	6.2	5.9	5.7	5.4	4.4
			7.0	8.6	8.3	7.9	7.5	8.2	7.8	7.5	7.2	7.3	7.0	6.8	6.5	6.5	6.3	6.0	5.8	4.8
			10.0	8.9	8.6	8.3	8.0	8.4	8.1	7.9	7.6	7.5	7.3	7.1	6.9	6.7	6.5	6.4	6.2	5.2

