

屋内照明器具特性

品番 (品名)	NNF 4 1 0 7 0	
光源	LDL40S . N / 14 / 26 (2600A) × 1 2600 . 0 1 m	
管理番号	K0133897 (*) DB 1	
BZ分類	BZ6	

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		19 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		78 %	壁	10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	4.9	3.6	2.8	2.3	4.6	3.5	2.8	2.2	4.2	3.2	2.6	2.1	3.8	3.0	2.4	2.0	1.7	
	中	0.81	0.8	5.8	4.6	3.7	3.1	5.5	4.4	3.6	3.0	5.0	4.0	3.4	2.9	4.5	3.7	3.2	2.7	2.3	
	否	0.77	1.0	6.4	5.2	4.4	3.8	6.1	5.0	4.2	3.7	5.5	4.6	4.0	3.5	5.0	4.3	3.7	3.3	2.8	
	下方投影面積	c m ²		1.25	6.9	5.9	5.0	4.4	6.6	5.6	4.9	4.3	6.0	5.2	4.6	4.0	5.4	4.8	4.2	3.8	3.3
等価発光面積	c m ²		1.5	7.3	6.3	5.6	4.9	7.0	6.1	5.4	4.8	6.4	5.6	5.0	4.5	5.8	5.2	4.7	4.2	3.7	
	c m ²		2.0	7.9	7.0	6.3	5.7	7.5	6.7	6.1	5.6	6.9	6.2	5.7	5.2	6.3	5.7	5.3	4.9	4.3	
取付高さ	器具間隔最大限		2.5	8.2	7.5	6.8	6.3	7.9	7.2	6.6	6.1	7.2	6.6	6.2	5.7	6.6	6.1	5.7	5.4	4.7	
	横方向 (A)	縦方向 (B)	3.0	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.5	7.5	7.0	6.5	6.1	6.8	6.4	6.1	5.7	5.1	
1.5m	2.2 m	2.15 m	4.0	8.8	8.3	7.8	7.3	8.5	8.0	7.5	7.1	7.8	7.4	7.0	6.7	7.2	6.8	6.5	6.2	5.5	
2	2.9	2.71	5.0	9.0	8.6	8.1	7.7	8.7	8.3	7.9	7.5	8.0	7.7	7.3	7.0	7.4	7.1	6.8	6.6	5.8	
2.5	3.61	3.29	7.0	9.3	8.9	8.6	8.3	9.0	8.6	8.3	8.0	8.3	8.0	7.7	7.5	7.7	7.4	7.2	7.0	6.2	
3	4.3	3.89	10.0	9.5	9.2	9.0	8.7	9.2	8.9	8.7	8.4	8.5	8.3	8.1	7.9	7.9	7.7	7.5	7.4	6.6	

