

屋内照明器具特性	
品番 (品名)	LGB58007U
光源	LDA5L-G/Z40E/S/W/2 ×1 485.0 l m
管理番号	K0123207(1)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.69	0.6	5.4	4.1	3.3	2.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.6	3.7	3.1	2.6	2.4
	中	0.67	0.8	6.4	5.2	4.3	3.8	6.2	5.0	4.3	3.7	5.8	4.8	4.1	3.6	5.4	4.6	4.0	3.5	3.3
	否	0.63	1.0	7.0	5.9	5.1	4.5	6.8	5.7	5.0	4.4	6.4	5.5	4.8	4.3	6.0	5.2	4.7	4.2	3.9
			1.25	7.6	6.6	5.8	5.2	7.4	6.4	5.7	5.1	6.9	6.1	5.5	5.0	6.5	5.8	5.3	4.9	4.5
下方投影面積		cm <sup>2</sup>	1.5	8.0	7.1	6.3	5.7	7.8	6.9	6.2	5.7	7.3	6.6	6.0	5.5	6.9	6.3	5.8	5.3	5.0
等価発光面積		cm <sup>2</sup>	2.0	8.6	7.8	7.1	6.6	8.3	7.6	7.0	6.5	7.9	7.2	6.7	6.3	7.4	6.9	6.5	6.1	5.7
取付高さ	器具間隔最大限		2.5	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.2	7.7	7.2	6.8	7.8	7.3	6.9	6.6	6.2
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.0	7.6	8.9	8.4	7.9	7.4	8.5	8.0	7.6	7.2	8.0	7.6	7.3	7.0	6.5
H <sub>m</sub>	1.30H <sub>m</sub>	1.30H <sub>m</sub>	4.0	9.5	9.0	8.6	8.2	9.3	8.8	8.4	8.0	8.8	8.4	8.1	7.8	8.4	8.1	7.8	7.5	7.0
			5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.7	8.4	9.0	8.7	8.4	8.1	8.6	8.3	8.1	7.8	7.4
			7.0	10.0	9.6	9.3	9.0	9.7	9.4	9.1	8.9	9.3	9.0	8.8	8.6	8.9	8.7	8.5	8.3	7.8
			10.0	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.5	9.3	9.1	8.9	9.1	8.9	8.8	8.6	8.1

