

屋内照明器具特性	
品番 (品名)	XS Z B 8 3 1 2 0
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0194321 (0) DR 1
B Z 分類	BZ1

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		40 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		39 %																							
保守率		良 中 否	0.67	0.6	45	38	33	30	42	36	32	29	37	32	29	26	32	28	26	24	20				
			0.63	0.8	52	45	40	37	49	43	39	36	42	38	35	32	37	34	31	29	25				
			0.56	1.0	57	50	46	42	53	47	44	41	46	42	39	37	40	37	35	33	27				
				1.25	60	55	51	47	56	52	48	45	49	46	43	41	42	40	38	36	30				
下方投影面積		cm ²	1.5	63	58	54	51	59	54	51	48	51	48	45	43	44	42	40	38	31					
等価発光面積		cm ²	2.0	66	62	59	56	62	58	55	53	54	51	49	47	46	44	43	41	33					
取付 高さ	器具間隔最大限		2.5	68	65	62	59	64	61	58	56	55	53	51	50	47	46	45	43	34					
	横方向 (A)		縦方向 (B)	3.0	70	67	64	62	65	62	60	58	56	54	53	51	48	47	46	45	35				
H m	1.32 H m	1.32 H m	4.0	71	69	67	65	67	65	63	61	58	56	55	54	49	48	47	47	36					
			5.0	73	71	69	67	68	66	64	63	58	57	56	55	50	49	48	48	37					
			7.0	74	72	71	70	69	68	66	65	59	59	58	57	51	50	49	49	37					
			10.0	75	74	73	72	70	69	68	67	60	60	59	58	51	51	50	50	38					

