

屋内照明器具特性	
品番 (品名)	XS Z B 1 1 1 6 1
光源	LLD2401VCB1 ×1 500.0 l m
管理番号	K0193966 (0) DB 1
B Z 分類	BZ1

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	57	50	45	42	56	49	45	42	55	49	45	42	53	48	45	42	41
			0.63	0.8	64	58	54	51	63	58	54	51	62	57	54	51	60	56	53	51	50
			0.56	1.0	69	64	60	57	68	63	60	57	66	62	59	57	65	61	58	56	55
				1.25	72	68	64	62	71	67	64	62	70	66	63	61	68	65	63	61	60
下方投影面積		c m ²		1.5	75	71	68	65	74	70	67	65	72	69	66	64	70	68	66	64	62
			等価発光面積	c m ²	2.0	77	74	72	69	77	74	71	69	75	72	70	68	73	71	69	68
取付 高さ	器具間隔最大限			2.5	79	76	74	72	78	76	74	72	76	74	73	71	75	73	72	70	69
	横方向 (A) 縦方向 (B)			3.0	80	78	76	74	79	77	75	74	78	76	74	73	76	74	73	72	70
H m	1.32 H m 1.32 H m			4.0	82	80	78	77	81	79	78	76	79	78	76	75	77	76	75	74	72
				5.0	82	81	80	78	81	80	79	78	80	79	78	77	78	77	76	75	74
				7.0	83	82	81	80	82	81	80	80	81	80	79	78	79	78	78	77	75
				10.0	84	83	82	82	83	82	82	81	81	81	80	80	80	79	79	78	76

