

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | XS Z B 1 6 1 6 1         |
| 光源       | LLD2401VCB1 ×1 500.0 l m |
| 管理番号     | K0193966 ( 0 ) DB 1      |
| B Z 分類   | BZ1                      |

| 器具効率     |                     | 79 %             | 反射率    | 天井               | 80 %          |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 %   |
|----------|---------------------|------------------|--------|------------------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-------|
|          |                     |                  |        | 壁                | 70            | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 %   |
|          |                     |                  |        | 床                | 10 %          |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 %   |
|          |                     |                  |        | 室指数              | 照明率 ( X0.01 ) |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z C M |
| 保守率      |                     | 良<br>中<br>否      | 0.67   | 0.6              | 57            | 50 | 45 | 42 | 56   | 49 | 45 | 42 | 55   | 49 | 45 | 42 | 53   | 48 | 45 | 42 | 41    |
|          |                     |                  | 0.63   | 0.8              | 64            | 58 | 54 | 51 | 63   | 58 | 54 | 51 | 62   | 57 | 54 | 51 | 60   | 56 | 53 | 51 | 50    |
|          |                     |                  | 0.56   | 1.0              | 69            | 64 | 60 | 57 | 68   | 63 | 60 | 57 | 66   | 62 | 59 | 57 | 65   | 61 | 58 | 56 | 55    |
|          |                     |                  |        | 1.25             | 72            | 68 | 64 | 62 | 71   | 67 | 64 | 62 | 70   | 66 | 63 | 61 | 68   | 65 | 63 | 61 | 60    |
| 下方投影面積   |                     | c m <sup>2</sup> |        | 1.5              | 75            | 71 | 68 | 65 | 74   | 70 | 67 | 65 | 72   | 69 | 66 | 64 | 70   | 68 | 66 | 64 | 62    |
|          |                     |                  | 等価発光面積 | c m <sup>2</sup> | 2.0           | 77 | 74 | 72 | 69   | 77 | 74 | 71 | 69   | 75 | 72 | 70 | 68   | 73 | 71 | 69 | 68    |
| 取付<br>高さ | 器具間隔最大限             |                  |        | 2.5              | 79            | 76 | 74 | 72 | 78   | 76 | 74 | 72 | 76   | 74 | 73 | 71 | 75   | 73 | 72 | 70 | 69    |
|          | 横方向 ( A ) 縦方向 ( B ) |                  |        | 3.0              | 80            | 78 | 76 | 74 | 79   | 77 | 75 | 74 | 78   | 76 | 74 | 73 | 76   | 74 | 73 | 72 | 70    |
| H m      | 1.32 H m 1.32 H m   |                  |        | 4.0              | 82            | 80 | 78 | 77 | 81   | 79 | 78 | 76 | 79   | 78 | 76 | 75 | 77   | 76 | 75 | 74 | 72    |
|          |                     |                  |        | 5.0              | 82            | 81 | 80 | 78 | 81   | 80 | 79 | 78 | 80   | 79 | 78 | 77 | 78   | 77 | 76 | 75 | 74    |
|          |                     |                  |        | 7.0              | 83            | 82 | 81 | 80 | 82   | 81 | 80 | 80 | 81   | 80 | 79 | 78 | 79   | 78 | 78 | 77 | 75    |
|          |                     |                  |        | 10.0             | 84            | 83 | 82 | 82 | 83   | 82 | 82 | 81 | 81   | 81 | 80 | 80 | 80   | 79 | 79 | 78 | 76    |

