

屋内照明器具特性

品番 (品名)	LGB72776				
光源	LED5000_70_780 x1		780.0 lm		
管理番号	K0135851(0)DB1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	99%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	56	44	36	30	55	43	35	30	52	42	35	30	50	41	34	30	28
	中	0.6	0.8	66	54	46	40	64	53	46	40	61	52	45	40	59	50	44	40	37
	否	0.56	1.0	73	62	54	48	71	61	53	48	68	59	52	47	65	57	51	47	44
			1.25	79	69	61	55	77	68	61	55	73	66	59	54	70	64	58	54	51
下方投影面積	cm ²		1.5	83	74	67	61	81	73	66	61	78	70	65	60	74	68	63	59	57
等価発光面積	cm ²		2.0	88	81	75	69	87	80	74	69	83	77	72	68	80	75	71	67	64
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	75	87	82	77	73	84	80	76	72	70
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	93	87	83	79	90	85	81	78	86	83	79	76	73
Hm	1.28Hm	1.28Hm	4.0	98	93	89	85	96	92	88	85	93	89	86	83	90	87	84	82	79
			5.0	100	96	92	89	98	95	91	88	95	92	89	87	92	90	87	85	82
			7.0	102	99	96	94	100	98	95	93	97	95	93	91	95	93	91	89	86
			10.0	104	102	100	98	102	100	98	97	99	98	96	95	97	95	94	93	90

