

屋内照明器具特性	
品番 (品名)	NTN88007B
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 7 9 4 7 3 (0) D R 1
B Z 分類	B Z 1

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																Z C M	
下方光束		80 %																			
保守率		良	0 . 6 7	0 . 6	67	63	59	57	67	62	59	57	66	62	59	57	65	61	59	57	56
		中	0 . 6 3	0 . 8	72	68	65	63	71	67	65	63	70	67	64	62	69	66	64	62	61
		否	0 . 5 6	1 . 0	75	71	68	66	74	71	68	66	73	70	68	66	72	69	67	65	64
				1 . 2 5	77	74	71	69	77	73	71	69	75	73	70	69	74	72	70	68	67
下方投影面積		c m ²		1 . 5	79	76	74	72	78	75	73	71	77	74	72	71	75	73	72	70	69
等価発光面積		c m ²		2 . 0	81	79	77	75	80	78	76	74	79	77	75	74	77	76	74	73	72
取付高さ	器具間隔最大限			2 . 5	82	80	78	77	81	79	78	76	80	78	77	76	78	77	76	75	73
	横方向 (A)		縦方向 (B)	3 . 0	83	81	80	78	82	81	79	78	81	79	78	77	79	78	77	76	74
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	84	83	81	80	83	82	81	80	81	80	79	79	80	79	78	78	76	
			5 . 0	85	84	82	82	84	83	82	81	82	81	80	80	80	80	79	78	77	
			7 . 0	85	84	84	83	84	84	83	82	83	82	81	81	81	81	80	80	78	
			10 . 0	86	85	85	84	85	84	84	83	83	83	82	82	81	81	81	80	78	

