

屋内照明器具特性

品番 (品名)	LGB72771										
光源	LED2700_70_660 x1 660.0 lm										
管理番号	K0135851(0)DB1										
BZ分類	BZ5										

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.5	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8
	中	0.6	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.9	5.0	4.4	4.0	3.7
	否	0.56	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.7	4.4
			1.25	7.9	6.9	6.1	5.5	7.7	6.8	6.1	5.5	7.3	6.6	5.9	5.4	7.0	6.4	5.8	5.4	5.1
下方投影面積	cm ²		1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.0	6.5	6.0	7.4	6.8	6.3	5.9	5.7
等価発光面積	cm ²		2.0	8.8	8.1	7.5	6.9	8.7	8.0	7.4	6.9	8.3	7.7	7.2	6.8	8.0	7.5	7.1	6.7	6.4
取付高さ	器具間隔最大限		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.7	7.3	8.4	8.0	7.6	7.2	7.0
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.6	8.3	7.9	7.6	7.3
Hm	1.28Hm	1.28Hm	4.0	9.8	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.2	7.9
			5.0	10.0	9.6	9.2	8.9	9.8	9.5	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.7	8.5	8.2
			7.0	10.2	9.9	9.6	9.4	10.0	9.8	9.5	9.3	9.7	9.5	9.3	9.1	9.5	9.3	9.1	8.9	8.6
			10.0	10.4	10.2	10.0	9.8	10.2	10.0	9.8	9.7	9.9	9.8	9.6	9.5	9.7	9.5	9.4	9.3	9.0

