

屋内照明器具特性

品番 (品名)	NNFS 4 1 6 0 5									
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1 m									
管理番号	K0130756(0)DB1									
BZ分類	BZ5									

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.81 0.77 0.68	0.6	52	40	32	27	50	39	32	27	48	38	31	27	46	37	31	26	24	
		0.8	61	49	42	36	59	49	41	36	57	47	41	36	54	46	40	35	33	
		1.0	67	56	48	43	65	55	48	43	62	54	47	42	60	52	47	42	40	
		1.25	73	63	55	50	71	62	55	49	68	60	54	49	65	58	53	49	46	
下方投影面積	c m ²	1.5	77	68	61	55	75	67	60	55	72	65	59	54	69	63	58	54	51	
		2.0	82	74	68	63	80	73	67	63	77	71	66	62	74	69	65	61	59	
取付高さ	器具間隔最大限		2.5	86	79	73	69	84	78	73	68	81	76	71	67	78	74	70	66	64
	横方向 (A)	縦方向 (B)	3.0	88	82	77	73	86	81	77	72	84	79	75	71	81	77	74	70	68
1.5m	2.02 m	2.13 m	4.0	91	87	83	79	90	86	82	78	87	83	80	77	84	81	78	76	73
2	2.66	2.69	5.0	93	89	86	83	92	88	85	82	89	86	83	81	86	84	82	79	77
2.5	3.31	3.26	7.0	96	93	90	88	94	92	89	87	92	89	87	85	89	87	85	84	81
3	3.95	3.85	10.0	97	95	93	91	96	94	92	91	94	92	90	89	91	90	89	87	85

