

屋内照明器具特性	
品番 (品名)	LGB72783
光源	LED2700_70_650 ×1 650.0 lm
管理番号	K0135851 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 1 % 下方光束 99 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %					10 %					10 %					10 %					0 %
					室指数	照明率 (X0.01)																				Z CM
保守率		良 中 否	0.63	0.6	56	44	36	30	55	43	35	30	52	42	35	30	50	41	34	30	28					
			0.6	0.8	66	54	46	40	64	53	46	40	61	52	45	40	59	50	44	40	37					
				1.0	73	62	54	48	71	61	53	48	68	59	52	47	65	57	51	47	44					
			0.56	1.25	79	69	61	55	77	68	61	55	73	66	59	54	70	64	58	54	51					
下方投影面積		cm ²		1.5	83	74	67	61	81	73	66	61	78	70	65	60	74	68	63	59	57					
			等価発光面積	cm ²	2.0	88	81	75	69	87	80	74	69	83	77	72	68	80	75	71	67	64				
取付	器具間隔最大限			2.5	92	85	80	75	90	84	79	75	87	82	77	73	84	80	76	72	70					
高さ	横方向 (A)		縦方向 (B)	3.0	94	89	84	80	93	87	83	79	90	85	81	78	86	83	79	76	73					
H m	1.28 H m		1.28 H m	4.0	98	93	89	85	96	92	88	85	93	89	86	83	90	87	84	82	79					
				5.0	100	96	92	89	98	95	91	88	95	92	89	87	92	90	87	85	82					
				7.0	102	99	96	94	100	98	95	93	97	95	93	91	95	93	91	89	86					
				10.0	104	102	100	98	102	100	98	97	99	98	96	95	97	95	94	93	90					

