

# 屋内照明器具特性

品番 (品名)	LGB73317									
光源	LED2700_70_350 x1					350.0 lm				
管理番号	K0148283(0)DB1									
BZ分類	BZ3/0.7/BZ2/1.4/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	66	56	49	45	65	55	49	45	63	54	49	45	61	54	48	45	43
	中	0.63	0.8	75	66	60	56	74	66	60	55	72	64	59	55	70	63	59	55	53
	否	0.56	1.0	81	73	67	63	80	72	67	63	78	71	66	62	75	70	65	62	60
			1.25	86	79	74	69	85	78	73	69	83	77	72	68	80	75	71	68	66
下方投影面積			1.5	90	83	78	74	88	82	77	73	86	81	76	73	83	79	75	72	70
等価発光面積			2.0	94	89	84	80	93	88	83	80	90	86	82	79	88	84	81	78	76
取付高さ	器具間隔最大限		2.5	97	92	88	85	95	91	87	84	93	89	86	83	90	87	85	82	80
	横方向 (A)	縦方向 (B)	3.0	99	94	91	88	97	93	90	87	95	91	89	86	92	90	87	85	83
Hm	1.15Hm	1.15Hm	4.0	101	98	95	92	100	97	94	91	97	94	92	90	95	92	91	89	86
			5.0	102	100	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89
			7.0	104	102	100	98	103	101	99	97	100	98	97	96	98	96	95	94	91
			10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93

