

屋内照明器具特性

品番 (品名)	LGB73411	
光源	LED3500_70_506 ×1	506.0 1m
管理番号	K0147259(0)DB1	
BZ分類	BZ1	

器具効率	99%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	99%	床		10%				10%				10%				10%				0%			
室指数	照明率 (X0.01)																			ZCM			
保守率	良 0.67	0.6	0.6	86	81	78	75	86	81	78	75	85	80	77	75	83	80	77	75	74			
	中 0.63		0.8	91	87	84	81	91	86	83	81	89	86	83	81	88	85	82	81	79			
	否 0.56		1.0	95	90	87	85	94	90	87	85	92	89	86	84	91	88	86	84	83			
下方投影面積	cm ²	等価発光面積	cm ²	1.25	97	93	91	88	96	93	90	88	95	92	90	88	93	91	89	87	86		
				1.5	99	96	93	91	98	95	93	91	96	94	92	90	95	93	91	89	88		
取付高さ	器具間隔最大限		Hm	0.37Hm	0.37Hm	2.5	102	100	98	96	101	99	97	96	99	98	96	95	98	96	95	94	92
	横方向 (A)	縦方向 (B)				3.0	103	101	99	98	102	100	99	97	100	99	97	96	98	97	96	95	93
Hm	0.37Hm	0.37Hm	4.0	104	103	101	100	103	102	101	99	101	100	99	98	99	98	97	97	95			
			5.0	105	104	102	101	104	103	102	101	102	101	100	99	100	99	98	98	95			
Hm	0.37Hm	0.37Hm	7.0	106	105	104	103	105	104	103	102	102	102	101	100	100	99	99	96				
			10.0	106	105	105	104	105	104	104	103	103	102	102	101	101	100	100	100	97			

