

屋内照明器具特性

品番 (品名)	NNN3 6 5 3 5									
光源	LED4000_85_1380 x1 1380.0 lm									
管理番号	K0187848 (1) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	7 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	93 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	5.4	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	3.9	3.3	2.8	4.7	3.8	3.2	2.7	2.5
	中	0.81	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.8	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.4
	否	0.77	1.0	7.0	5.9	5.1	4.5	6.8	5.8	5.0	4.5	6.4	5.6	4.9	4.4	6.1	5.3	4.7	4.3	4.0
			1.25	7.6	6.6	5.8	5.2	7.4	6.5	5.7	5.2	7.0	6.2	5.6	5.1	6.6	5.9	5.4	4.9	4.6
下方投影面積	cm ²		1.5	8.0	7.1	6.4	5.8	7.8	6.9	6.3	5.7	7.4	6.6	6.1	5.6	7.0	6.4	5.9	5.4	5.1
等価発光面積	cm ²		2.0	8.6	7.8	7.1	6.6	8.4	7.6	7.0	6.5	7.9	7.3	6.8	6.3	7.5	7.0	6.6	6.2	5.8
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.3	7.7	7.3	6.9	7.9	7.4	7.0	6.7	6.3
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.6	9.0	8.4	7.9	7.5	8.5	8.1	7.7	7.3	8.1	7.7	7.4	7.1	6.7
1.5m	1.94 m	1.89 m	4.0	9.5	9.0	8.6	8.2	9.3	8.9	8.4	8.1	8.9	8.5	8.1	7.8	8.5	8.2	7.9	7.6	7.2
2	2.58	2.48	5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.2	8.7	8.4	8.2	7.9	7.5
2.5	3.23	3.08	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.3	9.1	8.9	8.6	8.9	8.7	8.6	8.4	7.9
3	3.89	3.69	10.0	10.2	9.9	9.7	9.5	10.0	9.7	9.5	9.3	9.5	9.4	9.2	9.0	9.2	9.0	8.9	8.7	8.2

