

屋内照明器具特性

品番 (品名)	LGB73390				
光源	LED5000_70_423	x1	423.0 lm		
管理番号	K0150121(0)DB1				
BZ分類	BZ3/6.0/BZ2				

器具効率	99%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	62	51	44	40	61	51	44	40	59	50	44	39	57	49	43	39	38	
		0.8	73	63	56	51	71	62	56	51	69	61	55	51	67	60	55	51	49	
		1.0	79	70	64	59	78	70	64	59	75	68	63	59	73	67	62	58	57	
		1.25	85	77	71	67	83	76	71	66	81	75	70	66	78	73	69	66	64	
下方投影面積	c m ²	1.5	88	81	76	72	87	81	76	72	84	79	75	71	82	77	74	70	68	
		2.0	93	88	83	79	92	87	82	79	89	85	81	78	87	83	80	77	75	
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	87	84	92	89	85	83	90	87	84	82	79
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	87	94	91	88	86	92	89	87	85	82
H m	1.21H m	1.19H m	4.0	100	97	95	92	99	96	94	91	97	94	92	90	94	92	91	89	86
			5.0	102	99	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89
			7.0	104	102	100	99	102	101	99	98	100	99	97	96	98	97	95	94	92
			10.0	105	104	102	101	104	102	101	100	101	100	99	99	99	98	98	97	94

