

# 屋内照明器具特性

品番 (品名) **LGB73420**

光源 LED5000\_70\_553 ×1 553.0 lm

管理番号 K0147564 (0) DB 1

BZ分類 BZ1

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	99 %		室指数	照明率 ( X0.01 )																ZCM
保守率	良 0.67	0.6	86	81	78	76	86	81	78	75	85	80	77	75	84	80	77	75	74	
	中 0.63	0.8	92	87	84	82	91	87	84	81	90	86	83	81	88	85	83	81	80	
	否 0.56	1.0	95	91	88	85	94	90	87	85	92	89	87	85	91	88	86	85	83	
下方投影面積	cm <sup>2</sup>	1.25	97	94	91	89	96	93	91	89	95	92	90	88	93	91	89	88	86	
		1.5	99	96	93	91	98	95	93	91	96	94	92	90	95	93	91	90	88	
等価発光面積	cm <sup>2</sup>	2.0	101	98	96	95	100	98	96	94	98	96	95	93	97	95	94	92	91	
		2.5	102	100	98	97	101	99	98	96	99	98	96	95	98	96	95	94	92	
取付高さ	器具間隔最大限		3.0	103	101	100	98	102	100	99	98	100	99	98	96	98	97	96	95	93
	横方向 (A)	縦方向 (B)	4.0	104	103	101	100	104	103	102	101	99	101	100	99	98	99	98	97	95
Hm	0.35 Hm	0.35 Hm	5.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	95	
			7.0	106	105	104	103	104	104	103	102	102	102	101	100	100	99	99	96	
			10.0	106	105	105	104	105	104	104	103	103	102	102	101	101	100	100	97	

