

屋内照明器具特性	
品番 (品名)	XS Z B 1 6 3 0 7
光源	LLD2401VCB1 ×1 500.0 l m
管理番号	K0193060 (0) DB 1
B Z 分類	B Z 6

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 5 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		5 7 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 2	3 2	2 6	2 1	4 0	3 1	2 5	2 1	3 5	2 8	2 3	1 9	3 1	2 5	2 1	1 8	1 5	
			0 . 6	0 . 8	4 9	3 9	3 3	2 8	4 6	3 7	3 1	2 7	4 1	3 4	2 9	2 5	3 6	3 1	2 6	2 3	1 9	
			0 . 5 6	1 . 0	5 4	4 4	3 8	3 3	5 1	4 2	3 6	3 2	4 5	3 8	3 3	2 9	4 0	3 4	3 0	2 7	2 2	
				1 . 2 5	5 8	5 0	4 3	3 8	5 5	4 7	4 1	3 7	4 9	4 2	3 8	3 4	4 3	3 8	3 4	3 1	2 6	
下方投影面積		c m ²	1 . 5	6 1	5 3	4 7	4 2	5 8	5 1	4 5	4 1	5 1	4 6	4 1	3 7	4 6	4 1	3 7	3 4	2 8		
			等価発光面積		c m ²	2 . 0	6 6	5 9	5 3	4 8	6 2	5 6	5 1	4 6	5 5	5 0	4 6	4 3	4 9	4 5	4 2	3 9
取付 高さ	器具間隔最大限		2 . 5	6 8	6 2	5 7	5 3	6 5	5 9	5 5	5 1	5 8	5 4	5 0	4 6	5 2	4 8	4 5	4 2	3 5		
	横方向 (A)		縦方向 (B)		3 . 0	7 1	6 5	6 0	5 6	6 7	6 2	5 8	5 4	6 0	5 6	5 2	4 9	5 3	5 0	4 7	4 5	3 8
H m	0 . 9 4 H m		0 . 9 4 H m		4 . 0	7 3	6 9	6 5	6 1	7 0	6 5	6 2	5 9	6 2	5 9	5 6	5 4	5 6	5 3	5 1	4 9	4 1
					5 . 0	7 5	7 1	6 8	6 4	7 1	6 8	6 5	6 2	6 4	6 1	5 9	5 6	5 7	5 5	5 3	5 1	4 3
					7 . 0	7 7	7 4	7 1	6 9	7 3	7 1	6 8	6 6	6 6	6 4	6 2	6 0	5 9	5 8	5 6	5 4	4 6
					1 0 . 0	7 9	7 6	7 4	7 2	7 5	7 3	7 1	6 9	6 8	6 6	6 5	6 3	6 1	6 0	5 8	5 7	4 8

