

屋内照明器具特性

品番 (品名) **LGB76470**

光源 LED5000_70_755 ×1 755.0 lm

管理番号 K0151663(0)DB1

BZ分類 BZ1/0.7/BZ2

| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
|--------|-----------------|---------|------|-----|-----|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0% | 反射率 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 100% | | 壁 | 床 | 室指数 | 照明率 (X0.01) | ZCM | | | | | | | | | | | | | |
| 保守率 | 良 0.67 | 0.6 | 72 | 63 | 57 | 53 | 71 | 62 | 57 | 53 | 69 | 62 | 57 | 53 | 67 | 61 | 56 | 53 | 52 | |
| | 中 0.63 | 0.8 | 80 | 72 | 66 | 62 | 79 | 71 | 66 | 62 | 76 | 70 | 65 | 62 | 75 | 69 | 65 | 62 | 60 | |
| | 否 0.56 | 1.0 | 85 | 78 | 72 | 68 | 84 | 77 | 72 | 68 | 81 | 76 | 71 | 68 | 79 | 74 | 71 | 67 | 66 | |
| 下方投影面積 | cm ² | 1.25 | 89 | 83 | 78 | 74 | 88 | 82 | 78 | 74 | 86 | 81 | 77 | 73 | 84 | 79 | 76 | 73 | 71 | |
| | | 1.5 | 92 | 87 | 82 | 79 | 91 | 86 | 82 | 78 | 89 | 84 | 81 | 78 | 87 | 83 | 80 | 77 | 75 | |
| 等価発光面積 | cm ² | 2.0 | 96 | 92 | 88 | 85 | 95 | 91 | 87 | 84 | 93 | 89 | 86 | 83 | 90 | 87 | 85 | 82 | 80 | |
| | | 2.5 | 99 | 95 | 91 | 88 | 97 | 94 | 91 | 88 | 95 | 92 | 89 | 87 | 93 | 90 | 88 | 86 | 84 | |
| 取付高さ | 器具間隔最大限 | | 3.0 | 100 | 97 | 94 | 91 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 90 | 94 | 92 | 90 | 88 | 86 |
| | 横方向 (A) | 縦方向 (B) | 4.0 | 102 | 99 | 97 | 95 | 101 | 98 | 96 | 94 | 99 | 97 | 95 | 93 | 96 | 95 | 93 | 92 | 89 |
| Hm | 0.46Hm | 0.46Hm | 5.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 97 | 100 | 98 | 97 | 95 | 98 | 96 | 95 | 94 | 91 |
| | | | 7.0 | 105 | 103 | 102 | 100 | 103 | 102 | 101 | 99 | 101 | 100 | 99 | 98 | 99 | 98 | 97 | 96 | 93 |
| | | | 10.0 | 106 | 105 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 99 | 99 | 98 | 95 | |

