

屋内照明器具特性	
品番 (品名)	LGB78060
光源	LED2700_70_760 ×1 760.0 1m
管理番号	K0154590(0)D 1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	79	72	68	65	79	72	68	65	77	71	67	64	76	71	67	64	63
	中	0.63	0.8	86	80	76	72	85	79	75	72	84	78	75	72	82	78	74	72	70
	否	0.56	1.0	90	85	81	78	90	84	80	77	88	83	80	77	86	82	79	77	75
下方投影面積	cm <sup>2</sup>	1.25	94	89	85	82	93	88	85	82	91	87	84	82	89	86	83	81	80	
		1.5	96	92	89	86	95	91	88	85	93	90	87	85	92	89	86	84	83	
等価発光面積	cm <sup>2</sup>	2.0	99	96	93	90	98	95	92	90	96	93	91	89	94	92	90	88	86	
		2.5	101	98	96	93	100	97	95	93	98	96	94	92	96	94	92	91	89	
取付高さ	器具間隔最大限		3.0	102	100	98	96	101	99	97	95	99	97	95	94	97	95	94	93	91
Hm	横方向 (A)	縦方向 (B)	4.0	104	102	100	98	103	101	99	98	101	99	98	96	99	97	96	95	93
	0.49Hm	0.49Hm	5.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	97	94
			7.0	106	105	103	102	105	104	102	101	102	102	101	100	100	100	99	98	96
			10.0	107	106	105	104	105	104	103	103	103	102	101	101	101	100	99	97	97

