

屋内照明器具特性	
品番 (品名)	XS Z D 3 0 6 8 V
光源	L L D 3 4 1 1 V C B 1 × 1 7 0 0 . 0 l m
管理番号	K 0 1 9 2 0 3 7 (0) D B 1
B Z 分類	B Z 1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		83 %																					
保守率		良	0.67	0.6	77	74	72	70	77	73	71	70	76	73	71	70	75	73	71	70	69		
		中	0.63	0.8	80	77	75	74	80	77	75	74	79	76	75	73	78	76	74	73	73		
		否	0.56	1.0	82	80	78	76	82	79	77	76	81	79	77	76	80	78	77	75	75		
				1.25	84	82	80	78	83	81	79	78	82	80	79	78	81	79	78	77	76		
下方投影面積		c m ²		1.5	85	83	81	80	84	82	81	80	83	81	80	79	82	80	79	78	77		
等価発光面積		c m ²		2.0	86	84	83	82	85	84	83	82	84	83	82	81	83	82	81	80	79		
取付高さ	器具間隔最大限			2.5	87	86	84	83	86	85	84	83	85	84	83	82	83	82	82	81	80		
	横方向 (A)		縦方向 (B)	3.0	87	86	85	84	87	86	85	84	85	84	83	83	84	83	82	82	80		
H m	0.80 H m		0.80 H m	4.0	88	87	86	86	87	86	86	85	86	85	84	84	84	84	83	83	81		
				5.0	89	88	87	86	88	87	86	86	86	85	85	84	84	84	84	83	81		
				7.0	89	88	88	87	88	88	87	87	86	86	86	85	85	84	84	84	82		
				10.0	89	89	89	88	88	88	88	87	87	86	86	86	85	85	85	84	82		

