

屋内照明器具特性	
品番 (品名)	L S E B 3 1 1 2 Z
光源	LDG11L - G / 95 / W ×1 1370.0 l m
管理番号	K0147988 (0) DB 1
B Z 分類	B Z 6

器具効率	70 % 上方光束 4 % 下方光束 66 %	反射率	天井 80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X0.01) Z C M																
保守率	良 0.67	0.6	36	26	21	16	35	26	20	16	32	25	20	16	30	24	19	16	14
	中 0.63	0.8	43	34	27	23	41	33	27	23	38	31	26	22	36	30	25	22	20
	否 0.56	1.0	47	39	32	28	46	38	32	27	43	36	31	27	40	34	30	26	24
		1.25	51	43	37	33	50	42	37	32	47	40	36	32	44	39	34	31	28
下方投影面積 等価発光面積	c m ² c m ²	1.5	54	47	41	37	53	46	41	36	50	44	39	35	47	42	38	34	32
		2.0	59	52	47	43	57	51	46	42	54	49	45	41	51	46	43	40	37
		2.5	61	56	51	47	60	54	50	46	56	52	48	45	53	50	46	44	41
取付高さ	器具間隔最大限		3.0	63	58	54	50	62	57	53	49	58	54	51	48	55	52	49	47
	横方向 (A)	縦方向 (B)	4.0	66	62	58	55	64	60	57	54	61	58	55	52	58	55	53	51
H m	1.45 H m	1.45 H m	5.0	67	64	61	58	66	62	60	57	63	60	57	55	60	57	55	53
			7.0	69	66	64	62	68	65	63	61	65	62	60	59	62	60	58	57
			10.0	71	69	67	65	69	67	65	64	66	65	63	62	63	62	61	60

