

屋内照明器具特性

品番 (品名)	LGB81604									
光源	LED5000_70_495 x1					495.0 lm				
管理番号	K0139750(0)DB1									
BZ分類	BZ8/1.4/BZ7									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 50%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
				下方光束 50%	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.6	0.56	0.6	45	33	25	20	41	30	23	18	34	25	20	15	28	21	16	13	7
	中	0.6	0.6	0.6	0.6	0.8	54	42	34	28	49	38	31	26	41	32	26	22	33	26	22	18	11
	否	0.56	0.56	0.56	0.56	1.0	60	48	40	34	55	44	37	31	45	37	31	27	36	30	26	22	14
						1.25	65	54	46	40	60	50	43	37	49	42	36	32	40	34	30	26	21
下方投影面積 等価発光面積	c m ²		c m ²		1.5	69	59	51	45	63	55	48	42	53	46	40	36	43	38	33	30	26	20
	c m ²		c m ²		2.0	75	66	59	53	69	61	55	49	57	51	46	42	47	42	38	35	32	24
取付高さ	器具間隔最大限		H m		2.5	78	71	64	59	72	65	60	55	60	55	51	47	49	45	42	39	27	
	横方向 (A)	縦方向 (B)	1.52 H m	1.81 H m	3.0	81	74	68	63	75	69	63	59	63	58	54	50	51	48	45	42	29	
					4.0	84	79	74	69	78	73	69	64	66	62	58	55	54	51	49	46	32	
					5.0	87	82	77	73	80	76	72	68	68	64	61	59	56	54	51	49	35	
					7.0	89	85	82	79	83	79	76	73	70	68	65	63	58	56	54	53	38	
					10.0	91	88	86	83	85	82	80	78	72	70	68	67	60	59	57	56	40	

