

屋内照明器具特性

品番 (品名)	LGB81605									
光源	LED2700_70_436 ×1					436.0 lm				
管理番号	K0139751(0)DR1									
BZ分類	BZ8/1.4/BZ7									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 50%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
				下方光束 50%	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.6	0.56	0.6	45	33	25	20	41	31	23	18	34	26	20	15	28	21	16	13	7
	中	0.6	0.6	0.6	0.6	0.8	54	42	34	28	49	39	31	26	41	32	26	22	33	26	22	18	11
	否	0.56	0.56	0.56	0.56	1.0	60	48	40	34	55	44	37	31	45	37	31	27	36	30	26	22	14
						1.25	65	54	46	40	60	50	43	37	49	42	36	32	40	34	30	26	21
下方投影面積			cm ²		1.5	69	59	51	45	64	55	48	42	53	46	40	36	43	38	33	30	26	20
			cm ²		2.0	75	66	59	53	69	61	55	49	57	51	46	42	47	42	38	35	32	24
取付高さ	器具間隔最大限				2.5	78	71	64	59	72	65	60	55	60	55	51	47	49	45	42	39	27	
	横方向 (A)		縦方向 (B)		3.0	81	74	68	63	75	69	63	59	63	58	54	50	51	48	45	42	29	
H _m	1.51H _m		1.80H _m		4.0	84	79	74	69	78	73	69	64	66	62	58	55	54	51	49	46	32	
					5.0	87	82	77	73	80	76	72	68	68	64	61	59	56	54	51	49	35	
				7.0	89	85	82	79	83	79	76	73	70	68	65	63	58	56	55	53	38		
				10.0	91	88	86	83	85	82	80	78	72	70	68	67	60	59	57	56	40		

