

屋内照明器具特性	
品番 (品名)	LGB81650Z
光源	LDA4L-G-E17/Z40E/S/W/2 x1 440.0 1m
管理番号	K0140660(0)DB1
BZ分類	BZ7

器具効率	82%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	40%	床	10%				10%				10%				10%				0%				
下方光束	42%	室指数	照明率 (X0.01)																				ZCM
保守率	良 0.63 中 0.6 否 0.56	0.6	3.8	2.8	2.2	1.8	3.5	2.6	2.0	1.6	2.9	2.2	1.7	1.4	2.4	1.8	1.5	1.2	0.8				
		0.8	4.5	3.6	2.9	2.4	4.1	3.3	2.7	2.3	3.5	2.8	2.3	1.9	2.8	2.3	1.9	1.6	1.1				
		1.0	5.0	4.1	3.4	2.9	4.6	3.8	3.2	2.7	3.8	3.2	2.7	2.4	3.1	2.6	2.3	2.0	1.3				
		1.25	5.5	4.6	4.0	3.5	5.0	4.3	3.7	3.2	4.2	3.6	3.1	2.8	3.4	3.0	2.6	2.3	1.6				
下方投影面積	c m ²	1.5	5.8	5.0	4.4	3.9	5.3	4.6	4.1	3.6	4.4	3.9	3.5	3.1	3.6	3.2	2.9	2.6	1.8				
		2.0	6.2	5.5	5.0	4.5	5.7	5.1	4.6	4.2	4.8	4.4	4.0	3.6	4.0	3.6	3.3	3.0	2.1				
取付高さ	器具間隔最大限		2.5	6.5	5.9	5.4	5.0	6.0	5.5	5.0	4.6	5.1	4.7	4.3	4.0	4.2	3.9	3.6	2.4				
	横方向 (A)	縦方向 (B)	3.0	6.7	6.2	5.7	5.3	6.2	5.7	5.3	5.0	5.3	4.9	4.6	4.3	4.3	4.1	3.8	2.5				
H m	1.47 H m	1.39 H m	4.0	7.0	6.6	6.2	5.8	6.5	6.1	5.7	5.4	5.5	5.2	4.9	4.7	4.6	4.3	4.1	2.8				
			5.0	7.2	6.8	6.5	6.1	6.7	6.3	6.0	5.7	5.7	5.4	5.2	4.9	4.7	4.5	4.3	3.0				
			7.0	7.4	7.1	6.8	6.6	6.9	6.6	6.4	6.1	5.8	5.6	5.5	5.3	4.9	4.7	4.6	3.2				
			10.0	7.5	7.3	7.1	6.9	7.0	6.8	6.6	6.5	6.0	5.9	5.7	5.6	5.0	4.9	4.8	3.4				

