

屋内照明器具特性	
品番 (品名)	XSZR1011V
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0192057 (0) DB 1
BZ分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	45	40	36	34	45	40	36	34	44	39	36	34	43	39	36	34	33
			0.6	0.8	51	46	43	40	51	46	43	40	49	45	42	40	48	45	42	40	39
			0.56	1.0	55	50	47	45	54	50	47	45	53	49	46	44	51	48	46	44	43
			1.25	58	54	51	49	57	53	51	48	55	52	50	48	54	52	49	48	47	
下方投影面積		cm ²	1.5	59	56	53	51	59	55	53	51	57	55	52	51	56	54	52	50	49	
			2.0	62	59	57	55	61	58	56	55	60	57	56	54	58	56	55	54	52	
等価発光面積		cm ²	2.5	63	61	59	57	62	60	58	57	61	59	58	56	60	58	57	56	54	
			3.0	64	62	60	59	63	62	60	59	62	60	59	58	61	59	58	57	56	
H _m	1.07H _m	1.07H _m	4.0	65	64	62	61	65	63	62	61	63	62	61	60	62	61	60	59	58	
			5.0	66	65	64	63	65	64	63	62	64	63	62	61	62	62	61	60	59	
			7.0	67	66	65	64	66	65	64	64	65	64	63	63	63	63	62	62	60	
			10.0	67	67	66	66	67	66	65	65	65	65	64	64	64	63	63	63	61	

