

屋内照明器具特性	
品番 (品名)	XSZR1041L
光源	L LD2421LCB1 ×1 500.0 l m
管理番号	K0192059 (0) DB 1
BZ分類	BZ1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			Z C M
下方光束		83 %																					
保守率		良	0.63	0.6	68	62	59	56	67	62	58	56	66	61	58	56	65	61	58	56	55		
		中	0.6	0.8	73	68	65	63	73	68	65	63	71	67	64	62	70	67	64	62	61		
		否	1.0	1.0	77	72	69	67	76	72	69	67	75	71	68	66	73	70	68	66	65		
		0.56	1.25	80	76	73	71	79	75	73	70	77	74	72	70	76	73	71	70	68			
下方投影面積		c m ²	1.5	81	78	75	73	81	77	75	73	79	76	74	73	78	75	74	72	71			
			2.0	84	81	79	77	83	80	78	77	81	79	77	76	80	78	76	75	74			
取付高さ	器具間隔最大限		2.5	85	83	81	79	84	82	80	79	83	81	79	78	81	79	78	77	76			
	横方向 (A)		縦方向 (B)	3.0	86	84	82	81	85	83	82	80	83	82	81	79	82	81	79	78	77		
H m	0.54 H m	0.54 H m	4.0	87	86	84	83	86	85	84	83	84	83	82	81	83	82	81	80	78			
			5.0	88	87	85	84	87	86	85	84	85	84	83	83	83	83	82	81	79			
			7.0	89	88	87	86	88	87	86	85	86	85	85	84	84	84	83	83	81			
			10.0	89	89	88	87	88	88	87	87	86	86	85	85	85	84	84	84	81			

