

屋内照明器具特性	
品番 (品名)	XS Z B 8 3 1 1 8
光源	L L D 2 4 2 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 3 6 9 2 (0) D B 1
B Z 分類	B Z 1 / 1 . 1 / B Z 2 / 3 . 5 / B Z 3

器具効率		9 3 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		8 4 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束																							
保守率		良 中 否	0 . 6	6 6	5 8	5 3	5 0	6 5	5 8	5 3	5 0	6 3	5 6	5 2	4 9	6 0	5 5	5 1	4 9	4 7			
			0 . 6	7 3	6 5	6 0	5 7	7 1	6 5	6 0	5 6	6 8	6 3	5 9	5 6	6 6	6 1	5 8	5 5	5 3			
			1 . 0	7 7	7 0	6 5	6 2	7 5	6 9	6 5	6 1	7 2	6 7	6 3	6 0	6 9	6 5	6 2	5 9	5 7			
			0 . 5 6	1 . 2 5	8 1	7 5	7 0	6 6	7 9	7 3	6 9	6 6	7 6	7 1	6 7	6 4	7 3	6 9	6 6	6 3	6 0		
下方投影面積		c m ²	1 . 5	8 3	7 8	7 3	7 0	8 1	7 6	7 2	6 9	7 8	7 4	7 0	6 8	7 5	7 1	6 9	6 6	6 3			
			等価発光面積		c m ²	2 . 0	8 7	8 2	7 8	7 5	8 5	8 0	7 7	7 4	8 1	7 8	7 5	7 2	7 8	7 5	7 2	7 0	6 7
取付 高さ	器具間隔最大限					2 . 5	8 9	8 5	8 1	7 8	8 7	8 3	8 0	7 7	8 3	8 0	7 7	7 5	8 0	7 7	7 5	7 3	7 0
		横方向 (A)	縦方向 (B)	3 . 0	9 0	8 7	8 3	8 1	8 8	8 5	8 2	8 0	8 4	8 2	7 9	7 7	8 1	7 9	7 7	7 5	7 1		
H m	0 . 4 8 H m	0 . 5 1 H m	4 . 0	9 2	8 9	8 7	8 4	9 0	8 7	8 5	8 3	8 6	8 4	8 2	8 0	8 3	8 1	7 9	7 8	7 4			
			5 . 0	9 3	9 1	8 8	8 6	9 1	8 9	8 7	8 5	8 7	8 6	8 4	8 2	8 4	8 2	8 1	8 0	7 5			
			7 . 0	9 5	9 3	9 1	8 9	9 3	9 1	8 9	8 8	8 9	8 7	8 6	8 5	8 5	8 4	8 3	8 2	7 7			
			1 0 . 0	9 6	9 4	9 3	9 1	9 4	9 2	9 1	9 0	9 0	8 9	8 8	8 7	8 6	8 5	8 4	8 4	7 9			

