

屋内照明器具特性	
品番 (品名)	XS Z B 8 3 1 1 3
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0193246 (0) DB 1
B Z 分類	BZ3 / 1.8 / BZ4 / 6.0 / BZ5

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 0	4 1	3 6	3 2	4 8	4 0	3 5	3 1	4 5	3 8	3 4	3 0	4 2	3 6	3 2	2 9	2 7
			0 . 6	0 . 8	5 7	4 8	4 3	3 9	5 5	4 7	4 2	3 8	5 1	4 5	4 0	3 7	4 7	4 2	3 8	3 6	3 3
			0 . 5 6	1 . 0	6 1	5 4	4 8	4 4	5 9	5 2	4 7	4 3	5 5	4 9	4 5	4 2	5 1	4 6	4 3	4 0	3 7
				1 . 2 5	6 5	5 8	5 3	4 9	6 3	5 7	5 2	4 8	5 8	5 3	4 9	4 6	5 4	5 0	4 7	4 4	4 0
下方投影面積 等価発光面積		c m ²		1 . 5	6 8	6 2	5 7	5 3	6 6	6 0	5 5	5 2	6 1	5 6	5 3	4 9	5 7	5 3	5 0	4 7	4 3
				2 . 0	7 2	6 6	6 2	5 9	6 9	6 4	6 0	5 7	6 4	6 0	5 7	5 4	6 0	5 7	5 4	5 2	4 7
				2 . 5	7 4	7 0	6 6	6 2	7 2	6 7	6 4	6 1	6 7	6 3	6 0	5 8	6 2	5 9	5 7	5 5	5 0
				3 . 0	7 6	7 2	6 8	6 5	7 3	7 0	6 6	6 4	6 8	6 5	6 3	6 0	6 3	6 1	5 9	5 7	5 2
H m	1 . 0 7 H m	1 . 0 7 H m		4 . 0	7 8	7 5	7 2	6 9	7 5	7 2	7 0	6 7	7 0	6 8	6 6	6 4	6 5	6 3	6 2	6 0	5 5
				5 . 0	7 9	7 7	7 4	7 2	7 7	7 4	7 2	7 0	7 2	7 0	6 8	6 6	6 7	6 5	6 4	6 2	5 6
				7 . 0	8 1	7 9	7 7	7 5	7 8	7 6	7 5	7 3	7 3	7 2	7 0	6 9	6 8	6 7	6 6	6 5	5 9
				1 0 . 0	8 2	8 1	7 9	7 8	8 0	7 8	7 7	7 5	7 4	7 3	7 2	7 1	6 9	6 8	6 8	6 7	6 0

