

屋内照明器具特性	
品番 (品名)	L S E B 8 3 0 2 Z
光源	LDA4 L - G / S / K4 ×1 485.0 l m
管理番号	K0123336 (0) DB 1
B Z 分類	BZ4 / 1.8 / BZ5

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	50	41	35	31	48	40	34	30	45	38	33	29	42	36	31	28	26
			0.63	0.8	57	48	42	38	55	47	41	37	51	45	40	36	48	42	38	35	32
			0.56	1.0	62	54	48	43	60	52	47	42	56	49	44	41	52	46	42	39	36
				1.25	67	59	53	48	64	57	52	47	59	54	49	45	55	50	47	43	40
下方投影面積 等価発光面積		c m ² c m ²		1.5	70	62	57	52	67	60	55	51	62	57	52	49	58	53	50	47	42
				2.0	74	67	62	58	71	65	61	57	66	61	57	54	61	57	54	51	47
				2.5	76	71	66	62	74	69	64	61	68	64	61	58	64	60	57	55	50
				3.0	78	73	69	65	75	71	67	64	70	67	63	61	65	62	60	57	52
H m	1.26 H m	1.25 H m		4.0	81	77	73	70	78	74	71	68	73	70	67	64	68	65	63	61	55
				5.0	82	79	76	73	79	76	73	71	74	72	69	67	69	67	65	63	58
				7.0	84	81	79	77	81	79	77	74	76	74	72	70	71	69	68	66	60
				10.0	85	83	82	80	83	81	79	78	77	76	75	73	72	71	70	69	63

