

| | |
|----------|------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGB81785 |
| 光源 | LED2700_70_3780 x1 3780.0 lm |
| 管理番号 | K0161534(0)DR1 |
| BZ分類 | BZ8 |

| | | | | | | | | | | | | | | | | | | | |
|--------|------------------------------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 上方光束 | 50% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 下方光束 | 50% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 中 否 0.63 0.6 0.56 | 0.6 | 45 | 33 | 25 | 19 | 41 | 30 | 23 | 18 | 34 | 25 | 19 | 15 | 27 | 20 | 16 | 12 | 7 |
| | | 0.8 | 54 | 41 | 33 | 27 | 49 | 38 | 31 | 25 | 40 | 32 | 26 | 21 | 32 | 26 | 21 | 17 | 11 |
| | | 1.0 | 59 | 48 | 39 | 33 | 54 | 44 | 37 | 31 | 45 | 37 | 31 | 26 | 36 | 30 | 25 | 22 | 14 |
| | | 1.25 | 65 | 54 | 46 | 40 | 59 | 50 | 43 | 37 | 49 | 42 | 36 | 31 | 40 | 34 | 30 | 26 | 17 |
| 下方投影面積 | c m ² | 1.5 | 69 | 59 | 51 | 45 | 63 | 54 | 47 | 42 | 52 | 46 | 40 | 35 | 42 | 37 | 33 | 29 | 19 |
| | | 2.0 | 75 | 66 | 59 | 53 | 69 | 61 | 54 | 49 | 57 | 51 | 46 | 42 | 46 | 42 | 38 | 35 | 23 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 78 | 70 | 64 | 58 | 72 | 65 | 59 | 54 | 60 | 55 | 50 | 46 | 49 | 45 | 42 | 26 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 81 | 74 | 68 | 63 | 75 | 68 | 63 | 58 | 62 | 58 | 54 | 50 | 51 | 48 | 44 | 28 |
| 1.5m | 2.45m | 2.17m | 4.0 | 84 | 79 | 73 | 69 | 78 | 73 | 68 | 64 | 66 | 62 | 58 | 55 | 54 | 51 | 48 | 32 |
| 2 | 3.24 | 2.73 | 5.0 | 86 | 82 | 77 | 73 | 80 | 76 | 72 | 68 | 68 | 64 | 61 | 58 | 56 | 53 | 51 | 34 |
| 2.5 | 4.02 | 3.31 | 7.0 | 89 | 85 | 82 | 78 | 83 | 79 | 76 | 73 | 70 | 67 | 65 | 63 | 58 | 56 | 54 | 37 |
| 3 | 4.81 | 3.91 | 10.0 | 91 | 88 | 86 | 83 | 85 | 82 | 80 | 77 | 72 | 70 | 68 | 66 | 60 | 59 | 57 | 40 |

