

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | LGB84395          |          |
| 光源      | LED5000_70_970 x1 | 970.0 lm |
| 管理番号    | K0135904(0)DB1    |          |
| BZ分類    | BZ3               |          |

|        |                 |         |              |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    |     |    |
|--------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%            | 天井      | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |    |    | 0%  |    |
|        |                 | 壁       | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%              | 床       | 10%          |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%            | 室指数     | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    | ZCM |    |
| 保守率    | 良               | 0.67    | 0.6          | 63  | 52  | 45  | 40  | 62  | 51  | 45  | 40  | 59  | 50  | 44 | 40  | 57 | 49 | 44 | 40  | 38 |
|        | 中               | 0.63    | 0.8          | 73  | 64  | 57  | 52  | 72  | 63  | 57  | 52  | 70  | 62  | 56 | 52  | 68 | 61 | 56 | 52  | 50 |
|        | 否               | 0.56    | 1.0          | 80  | 72  | 65  | 61  | 79  | 71  | 65  | 60  | 76  | 69  | 64 | 60  | 74 | 68 | 63 | 60  | 58 |
|        |                 |         | 1.25         | 86  | 78  | 72  | 68  | 84  | 77  | 72  | 68  | 82  | 76  | 71 | 67  | 79 | 74 | 70 | 67  | 65 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5          | 89  | 82  | 77  | 73  | 88  | 82  | 77  | 73  | 85  | 80  | 76 | 72  | 83 | 78 | 75 | 71  | 69 |
|        | 等価発光面積          |         | 2.0          | 94  | 88  | 84  | 80  | 92  | 87  | 83  | 80  | 90  | 86  | 82 | 79  | 87 | 84 | 81 | 78  | 76 |
| 取付高さ   | 器具間隔最大限         |         | 2.5          | 97  | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 93  | 89  | 86 | 83  | 90 | 87 | 85 | 82  | 80 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0          | 99  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 92  | 89 | 86  | 92 | 90 | 87 | 85  | 83 |
| Hm     | 1.27Hm          | 1.27Hm  | 4.0          | 101 | 98  | 95  | 92  | 100 | 97  | 94  | 92  | 97  | 95  | 92 | 90  | 95 | 93 | 91 | 89  | 87 |
|        |                 |         | 5.0          | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 94  | 99  | 97  | 95 | 93  | 96 | 95 | 93 | 92  | 89 |
|        |                 |         | 7.0          | 104 | 102 | 100 | 99  | 103 | 101 | 99  | 98  | 100 | 99  | 97 | 96  | 98 | 97 | 96 | 94  | 92 |
|        |                 |         | 10.0         | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 101 | 100 | 99 | 98  | 99 | 98 | 98 | 97  | 94 |

