

屋内照明器具特性

品番 (品名)	LGB51770														
光源	LED5000_70_535 x1					535.0 lm									
管理番号	K0135839(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数	照明率 (X0.01)																ZCM		
下方光束	96%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26		
		0.8	65	54	46	40	64	53	45	39	60	51	44	39	57	49	43	38	36		
		1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43		
		1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	50		
下方投影面積	c m ²	1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	55		
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62		
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	71	67	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	85	81	78	75	71	
H m	1.29 H m	1.29 H m	4.0	97	92	88	85	95	91	87	84	91	88	85	82	88	85	82	80	76	
			5.0	99	95	92	89	97	94	90	87	93	91	88	85	90	88	85	83	80	
			7.0	101	98	96	93	99	97	94	92	96	94	92	90	93	91	89	87	84	
			10.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87	

