

屋内照明器具特性

品番 (品名)	NTS32813S+NTS92151
光源	LED3000_70_670 x1 670.0 l m
管理番号	K0156488 (1) DJ 1
BZ分類	BZ1

器具効率			1 0 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %							
上方光束					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
下方光束					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %							
					室指数	照明率 (X 0 . 0 1)																Z C M							
保守率			良	0 . 6 7	0 . 6	1 0	2 1	0 0	9 8	9 7	1 0	2 1	0 0	9 8	9 7	1 0	1 9	9 8	9 7	1 0	1 9	9 8	9 7	9 6					
			中	0 . 6 3	0 . 8	1 0	4 1	0 2	1 0	0 9	9 1	1 0	4 1	0 1	1 0	0 9	9 1	1 0	3 1	0 1	1 0	0 9	9 1	1 0	2 1	0 0	9 9	9 8	9 8
			否	0 . 5 6	1 . 0	1 0	5 1	0 3	1 0	2 1	0 0	1 0	5 1	0 3	1 0	1 1	0 0	1 0	3 1	0 2	1 0	1 1	0 0	1 0	3 1	0 1	1 0	0 0	9 9
下方投影面積 等価発光面積			c m ²	1 . 2 5	1 0	6 1	0 4	1 0	3 1	0 2	1 0	5 1	0 4	1 0	2 1	1 0	4 1	0 3	1 0	2 1	1 0	1 0	3 1	0 2	1 0	1 1	0 0	9 9	
				1 . 5	1 0	7 1	0 5	1 0	4 1	0 3	1 0	6 1	0 4	1 0	3 1	0 2	1 0	5 1	0 3	1 0	2 1	1 0	2 1	0 3	1 0	2 1	0 2	1 0	1 1
			c m ²	2 . 0	1 0	8 1	0 6	1 0	5 1	0 4	1 0	7 1	0 5	1 0	4 1	0 3	1 0	5 1	0 4	1 0	3 1	0 3	1 0	4 1	0 3	1 0	2 1	0 2	1 0
取付高さ	器具間隔最大限			2 . 5	1 0	8 1	0 7	1 0	6 1	0 5	1 0	7 1	0 6	1 0	5 1	0 4	1 0	6 1	0 5	1 0	4 1	0 3	1 0	4 1	0 3	1 0	3 1	0 2	1 0
	横方向 (A)		縦方向 (B)	3 . 0	1 0	9 1	0 7	1 0	6 1	0 6	1 0	8 1	0 7	1 0	6 1	0 5	1 0	6 1	0 5	1 0	4 1	0 4	1 0	4 1	0 4	1 0	3 1	0 3	1 0
H _m	0 . 2 5 H _m		0 . 2 5 H _m	4 . 0	1 0	9 1	0 8	1 0	7 1	0 7	1 0	8 1	0 7	1 0	6 1	0 6	1 0	6 1	0 6	1 0	5 1	0 5	1 0	4 1	0 4	1 0	4 1	0 3	1 0
				5 . 0	1 0	9 1	0 9	1 0	8 1	0 7	1 0	8 1	0 8	1 0	7 1	0 7	1 0	6 1	0 6	1 0	5 1	0 5	1 0	5 1	0 4	1 0	4 1	0 3	1 0
				7 . 0	1 1	1 0	0 9	1 0	9 1	0 8	1 0	9 1	0 8	1 0	8 1	0 7	1 0	7 1	0 6	1 0	6 1	0 6	1 0	5 1	0 4	1 0	4 1	0 4	1 0
				1 0 . 0	1 1	1 0	1 0	1 0	9 1	0 9	1 0	9 1	0 9	1 0	8 1	0 8	1 0	7 1	0 7	1 0	6 1	0 6	1 0	5 1	0 5	1 0	4 1	0 4	1 0

