

屋内照明器具特性

品番 (品名)	LGB51776										
光源	LED5000_70_530 x1					530.0 lm					
管理番号	K0135839(0)DB1										
BZ分類	BZ5										

器具効率	100%	天井	80%				70%				50%				30%				0%				
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				床	10%				10%				10%				10%				0%		
上方光束	4%	室指数																					
下方光束	96%	照明率 (X0.01)																					
保守率	良 中 否	0.63	0.6	0.56	ZCM																		
		0.6	0.6	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26		
		0.6	0.6	0.6	65	54	46	40	64	53	45	39	60	51	44	39	57	49	43	38	36		
		0.56	0.56	0.56	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43		
下方投影面積	c m ²	1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	50				
		1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	55				
等価発光面積	c m ²	2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62				
		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	71	67				
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	88	84	80	76	85	81	78	75	71			
	横方向 (A)	縦方向 (B)	3.0	97	92	88	85	95	91	87	84	91	88	85	82	88	85	82	80	76			
H m	1.29 H m	1.29 H m	4.0	99	95	92	89	97	94	90	87	93	91	88	85	90	88	85	83	80			
			5.0	101	98	96	93	99	97	94	92	96	94	92	90	93	91	89	87	84			
			7.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87			
			10.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87			

