

屋内照明器具特性

品番 (品名)	LGB51777														
光源	LED2700_70_440 x1 440.0 l m														
管理番号	K0135839(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26
	中	0.6	0.8	65	54	46	40	64	53	45	39	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43
			1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	50
下方投影面積	cm ²		1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	55
等価発光面積	cm ²		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	71	67
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	85	81	78	75	71
Hm	1.29Hm	1.29Hm	4.0	97	92	88	85	95	91	87	84	91	88	85	82	88	85	82	80	76
			5.0	99	95	92	89	97	94	90	87	93	91	88	85	90	88	85	83	80
			7.0	101	98	96	93	99	97	94	92	96	94	92	90	93	91	89	87	84
			10.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87

