

屋内照明器具特性

品番 (品名)	LGB52632									
光源	LED5000_70_1720 x1 1720.0 1m									
管理番号	K0147580(0)DB1									
BZ分類	BZ6/0.7/BZ5/3.5/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 12%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	88%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	53	41	33	27	51	39	32	27	47	37	31	26	44	35	29	25	22
	中	0.6	0.8	62	50	42	36	60	49	41	36	56	46	40	35	52	44	38	34	30
	否	0.56	1.0	69	57	49	43	66	56	48	42	62	53	46	41	57	50	44	40	36
			0.56	1.25	75	64	56	50	72	62	55	49	67	59	53	48	62	56	50	46
下方投影面積	cm ²		1.5	79	69	61	55	76	67	60	54	71	63	57	53	66	60	55	51	46
等価発光面積	cm ²		2.0	84	76	69	64	81	74	68	62	76	70	65	60	71	66	62	58	53
取付高さ	器具間隔最大限		2.5	88	81	74	69	85	78	73	68	80	74	69	65	75	70	66	63	58
	横方向 (A)	縦方向 (B)	3.0	90	84	78	74	88	82	77	72	82	77	73	69	77	73	70	66	61
Hm	1.29Hm	1.29Hm	4.0	94	88	84	80	91	86	82	78	86	82	78	75	81	77	74	72	66
			5.0	96	91	87	84	93	89	85	82	88	84	81	78	83	80	77	75	69
			7.0	98	95	92	89	96	92	89	87	90	88	85	83	85	83	81	79	73
			10.0	100	98	95	93	98	95	93	91	92	90	89	87	88	86	84	83	77

