

屋内照明器具特性

品番 (品名)	LGBX10001														
光源	LED2700_70_490 x1 490.0 lm														
管理番号	K0152468(0)DB1														
BZ分類	BZ6/0.7/BZ5														

器具効率	90%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	10%	床	10%				10%				10%				10%				0%	
下方光束	80%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	47	36	29	23	45	35	28	23	42	33	27	22	39	31	26	22	19
	中	0.63	0.8	56	45	38	33	54	44	37	32	51	42	36	31	47	40	35	30	28
	否	0.56	1.0	62	52	45	40	60	51	44	39	56	48	42	38	52	46	41	37	34
			1.25	68	59	52	47	66	57	51	46	61	54	49	44	57	52	47	43	40
下方投影面積		cm ²	1.5	72	63	57	52	69	62	56	51	65	59	54	49	61	56	51	48	44
等価発光面積		cm ²	2.0	77	70	64	60	75	68	63	59	70	65	60	57	66	62	58	55	51
取付高さ	器具間隔最大限		2.5	80	74	69	65	78	72	68	64	73	69	65	61	69	65	62	59	55
	横方向 (A)	縦方向 (B)	3.0	83	77	73	69	80	75	71	68	76	72	68	65	71	68	65	63	58
H _m	1.54H _m	1.54H _m	4.0	85	81	78	74	83	79	76	73	79	75	73	70	74	72	69	67	63
			5.0	87	84	81	78	85	82	79	76	80	78	75	73	76	74	72	70	65
			7.0	89	87	84	82	87	85	82	80	83	81	79	77	79	77	75	74	69
			10.0	91	89	87	85	89	87	85	84	84	83	82	80	80	79	78	77	72

