

# 屋内照明器具特性

|         |                             |  |
|---------|-----------------------------|--|
| 品番 (品名) | LGBX3189                    |  |
| 光源      | LED6200_70_5499 x1 5499.0lm |  |
| 管理番号    | K0150065(0)D1               |  |
| BZ分類    | BZ5                         |  |

|        |                  |         |                  |      |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |     |
|--------|------------------|---------|------------------|------|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|-----|
| 器具効率   | 100%             | 天井      | 80%              |      |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |     |
|        | 上方光束<br>28%      |         | 下方光束<br>72%      | 反射率  | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30 | 10 | 0%  |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    | ZCM |
| 保守率    | 良                | 0.63    | 0.6              | 52   | 40 | 32 | 26  | 49 | 38 | 31 | 26  | 44 | 35 | 28 | 24  | 39 | 32 | 26 | 22 | 19 |     |
|        | 中                | 0.6     | 0.8              | 61   | 49 | 41 | 36  | 58 | 47 | 40 | 35  | 52 | 43 | 37 | 32  | 46 | 39 | 34 | 30 | 26 |     |
|        | 否                | 0.56    | 1.0              | 67   | 56 | 49 | 43  | 64 | 54 | 47 | 41  | 57 | 49 | 43 | 39  | 51 | 45 | 40 | 36 | 31 |     |
|        |                  |         |                  | 1.25 | 73 | 63 | 56  | 50 | 69 | 60 | 53  | 48 | 62 | 55 | 49  | 45 | 56 | 50 | 45 | 42 | 36  |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 77   | 68 | 61 | 55  | 73 | 65 | 58 | 53  | 66 | 59 | 54 | 50  | 59 | 54 | 50 | 46 | 39 |     |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0  | 82 | 75 | 69  | 63 | 78 | 72 | 66  | 61 | 71 | 65 | 61  | 57 | 64 | 59 | 56 | 52 | 45  |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 86   | 79 | 74 | 69  | 82 | 76 | 71 | 67  | 74 | 69 | 65 | 62  | 67 | 63 | 60 | 57 | 49 |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 88   | 83 | 78 | 73  | 84 | 79 | 75 | 71  | 76 | 72 | 69 | 65  | 69 | 66 | 63 | 60 | 52 |     |
| Hm     | 1.28Hm           | 1.26Hm  | 4.0              | 92   | 87 | 83 | 79  | 88 | 83 | 80 | 76  | 80 | 76 | 73 | 70  | 72 | 69 | 67 | 65 | 56 |     |
|        |                  |         | 5.0              | 94   | 90 | 86 | 83  | 89 | 86 | 83 | 80  | 81 | 79 | 76 | 74  | 74 | 72 | 70 | 68 | 59 |     |
|        |                  |         | 7.0              | 96   | 93 | 90 | 88  | 92 | 89 | 87 | 84  | 84 | 82 | 80 | 78  | 76 | 75 | 73 | 71 | 62 |     |
|        |                  |         | 10.0             | 98   | 96 | 93 | 92  | 94 | 92 | 90 | 88  | 86 | 84 | 82 | 81  | 78 | 77 | 76 | 74 | 64 |     |

