

# 屋内照明器具特性

品番 (品名)	LGBZ1435									
光源	LED6200_70_4299 x1 4299.0 lm									
管理番号	K0145469(0)DB1									
BZ分類	BZ9/0.7/BZ8/1.8/BZ7/6.0/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 6%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 94%	10%				10%				10%				10%			
室指数	照明率 ( X0.01) ZCM																			
保守率	良	0.63	0.6	47	33	23	17	45	32	23	17	42	30	22	16	39	28	21	16	13
	中	0.6	0.8	56	42	32	25	54	41	31	25	50	38	30	24	46	36	29	23	20
	否	0.56	1.0	62	48	39	31	60	47	38	31	56	45	36	30	52	42	35	29	26
			1.25	68	55	46	38	66	54	45	38	61	51	43	37	57	48	41	36	32
下方投影面積	c m <sup>2</sup>		1.5	73	61	51	44	70	59	50	43	66	56	48	42	61	53	46	41	37
	等価発光面積		c m <sup>2</sup>	2.0	79	69	60	53	77	67	59	52	72	64	57	51	68	61	55	49
取付高さ	器具間隔最大限		2.5	84	74	67	60	81	73	65	59	77	69	63	57	72	66	60	56	52
	横方向 (A)	縦方向 (B)	3.0	87	79	72	65	85	77	70	64	80	73	68	63	75	70	65	61	57
H m	1.71H m	1.77H m	4.0	91	85	79	73	89	83	77	72	84	79	74	70	80	76	72	68	63
			5.0	94	88	83	78	92	86	82	77	87	83	79	75	83	79	76	73	68
			7.0	97	93	89	85	95	91	87	84	91	88	84	81	87	84	81	79	74
			10.0	100	97	94	91	98	95	92	89	94	91	89	87	90	88	86	84	79

