

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNN57004+NEL4500EV           |
| 光源       | LED3500_85_7390 ×1 7390.0 lm |
| 管理番号     | K0193070 ( 0 ) DB 1          |
| BZ分類     | BZ5                          |

| 器具効率     |           | 100 %           | 反射率    | 天井   | 80 %            |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|--------|------|-----------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |        | 壁    | 70              | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |        | 床    | 10 %            |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |        | 室指数  | 照明率 ( X0.01 )   |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    | ZCM |
| 保守率      |           | 良<br>中<br>否     | 0.77   | 0.6  | 55              | 43  | 35 | 30 | 53   | 42 | 34 | 29 | 49   | 40 | 33 | 28 | 46   | 38 | 32 | 28 | 25  |
|          |           |                 | 0.72   | 0.8  | 64              | 53  | 45 | 39 | 62   | 51 | 44 | 39 | 58   | 49 | 42 | 37 | 54   | 46 | 41 | 36 | 33  |
|          |           |                 | 0.68   | 1.0  | 71              | 60  | 52 | 46 | 68   | 58 | 51 | 46 | 63   | 55 | 49 | 44 | 59   | 52 | 47 | 42 | 39  |
|          |           |                 |        | 1.25 | 76              | 66  | 59 | 53 | 74   | 65 | 58 | 52 | 69   | 61 | 55 | 50 | 64   | 58 | 53 | 49 | 44  |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5    | 80   | 71              | 64  | 59 | 77 | 69   | 63 | 57 | 72 | 65   | 60 | 55 | 67 | 62   | 57 | 53 | 49 |     |
|          |           |                 | 等価発光面積 |      | cm <sup>2</sup> | 2.0 | 86 | 78 | 72   | 66 | 83 | 76 | 70   | 65 | 77 | 72 | 67   | 63 | 72 | 68 | 64  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 89   | 82              | 77  | 72 | 86 | 80   | 75 | 71 | 81 | 76   | 71 | 68 | 76 | 72   | 68 | 65 | 60 |     |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 91   | 86              | 81  | 76 | 89 | 83   | 79 | 75 | 83 | 79   | 75 | 71 | 78 | 74   | 71 | 68 | 63 |     |
| 1.5m     | 1.89 m    | 2.1 m           | 4.0    | 95   | 90              | 86  | 82 | 92 | 87   | 84 | 80 | 86 | 83   | 79 | 77 | 81 | 78   | 76 | 73 | 67 |     |
| 2        | 2.48      | 2.6             | 5.0    | 97   | 93              | 89  | 86 | 94 | 90   | 87 | 84 | 88 | 85   | 82 | 80 | 83 | 81   | 78 | 76 | 70 |     |
| 2.5      | 3.08      | 3.14            | 7.0    | 99   | 96              | 93  | 90 | 96 | 93   | 91 | 88 | 91 | 88   | 86 | 84 | 85 | 84   | 82 | 80 | 74 |     |
| 3        | 3.68      | 3.69            | 10.0   | 101  | 98              | 96  | 94 | 98 | 96   | 94 | 92 | 92 | 91   | 89 | 88 | 87 | 86   | 85 | 83 | 77 |     |

